

# MIRRORS



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11



Fig. 12



Fig. 13



Fig. 14

## Mirror Assemblies

Part #	Fig.#	Mirror Size	Description
<b>West Coast</b>			
603862	1	7" x 16"	Retractable Stainless Steel Assembly
<b>Universal</b>			
604614	2	5" x 8"	Custom Ford Swing-Away Design
611500	3	7 1/2" x 10 1/2"	Stainless Steel Brackets w/ 12"

## Mirror Heads

Part #	Fig.#	Mirror Size	Description
<b>Standard</b>			
600604	4	6" x 16"	Brushed Aluminum Finish
600932	4	6" x 16"	Bright Anodized Aluminum
610321	5	6" x 16"	OEM Style Aluminum
600807	5	7" x 16"	OEM Style Polished Stainless Steel
601272	5	7" x 16"	OEM Style Polished Stainless Steel
610226	6	7" x 16"	OEM Style Polished Stainless Steel
<b>Heated</b>			
601285	5	7" x 16"	OEM Style Polished Stainless Steel
<b>Heated and Motorized</b>			
607004	7	7" x 16"	OEM Style Polished Stainless Steel Mirror Has Horizontal and Vertical Adj.
<b>Light Duty</b>			
604768	8	6" x 9"	Stainless Steel OEM Replacement
610815	9	6 1/2" x 6"	Stainless Steel w/ Convex Mirror
610829	10	6 1/2" x 10"	Stainless Steel w/ Flat Mirror
610809	11	7 1/2" x 10 1/2"	Bright Anodized Aluminum
611600	12	7 1/2" x 10 1/2"	Polished Stainless Steel Head w/Arm

## Spot Mirrors

Part #	Fig.#	Mirror Size	Description
604770	13	4" x 5 1/2"	Stick-On Rectangular Convex
604771	14	2"	Stick-On Round Convex
604772	14	3"	Stick-On Round Convex
604773	14	3 3/4"	Stick-On Round Convex

# MIRRORS

## Convex Mirrors

Part #	Fig.#	Size	Stud Mnt.	Description
610148	1	5"	Center	Polished Stainless Steel
610456	2	5 1/2" x 7 1/2"	Center	Rectangular Anodized Aluminum
610191	1	6"	Center	Polished Stainless Steel
610193	1	6"	Center	Polished Stainless Steel w/ "J" Brkt.
610406	3	6"	Center	Steel Coated Black
604976	1	7 1/2"	Center	Polished Stainless Steel
609838	5	7 1/2"	Offset	Polished Stainless Steel w/ "J" Brkt.
604898	1	8"	Center	Polished Stainless Steel
610551	4	8"	Offset	Polished Stainless Steel
610673	1	8"	Center	Polished Stainless Steel w/ "J" Brkt.
610556	---	8"	Offset	Polished Stainless Steel, Heated
609898	5	8 1/2"	Offset	Polished Stainless Steel w/ "J" Brkt.
609946	5	8 1/2"	Offset	Polished Stainless Steel, Heated
604947	---	12"	Center	Black Plastic Back



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5

## Safety Assemblies

Part #	Fig.#	Description
<b>Bracket Only</b>		
608100	6	Polished Stainless Steel Horizontal Mount Cross-View
608135	7	Polished Stainless Steel Vertical Mount Cross-View



Fig. 6



Fig. 7

### Mirror Assembly

610775	8	8" Bubble Mirror For Safety Cross-View Assemblies
--------	---	---



Fig. 8

## Mirror Accessories

Part #	Fig.#	Description
601690	9	3" Stainless Steel Extension
605755	10	Mounting Arm
607962	11	2-Piece Clamp 3/4" O.D.
607969	12	J-Bracket
608351	13	4" Stainless Steel Bracket
608359	13	6" Stainless Steel Bracket
101181	---	5 1/2" x 14 1/2" Heater Pad



Fig. 9



Fig. 10



Fig. 11



Fig. 12



Fig. 13

# TRUCK SEATING



Fig. 1

## Viking T-Bar Seating

Part #	Fig.#	Color / Material	Description
0042764-001	1	Black / Vinyl	Low Back w/ Riser (No Armrest)
0108188-001	1	Black / Vinyl	Low Back Heavy Duty w/ Armrest

**Viking T-Bar seats offer a low-profile design and a 4" ride zone.**

## Air Suspension Seating

Part #	Fig.#	Color / Material	Description
<b>T915 Series</b>			
2339130-550	2	Black / Cloth	Mid Back Seat (No Armrest)
2339130-552	2	Gray / Cloth	Mid Back Seat (No Armrest)
2339199-550	2	Black / Cloth	Mid Back Seat w/ Air Lumbar (No Armrest)

**Bostrom T915 air suspension seats offer 6" of ride zone and 9.5" of fore and aft adjustment.**

### T910

2343070-550	3	Black / Cloth	Mid Back Seat (No Armrest)
2343070-552	3	Gray / Cloth	Mid Back Seat (No Armrest)

**Bostrom T910 air suspension seats offer 3.8" of ride zone, 9.5" of fore and aft adjustment and a mechanical lumbar support.**

### T910SC

2348005-550	4	Black / Cloth	Low Profile Mid Back Seat (No Armrest)
2348005-552	4	Gray / Cloth	Low Profile Mid Back Seat (No Armrest)
2348014-418	4	Gray / Cordura	Low Profile Mid Back w/ Dual Armrest and Driver Swivel

**Bostrom T910SC air suspension seats offer 3.8" of ride zone and 9.5" of fore and aft adjustment. Also includes 12V self contained air compressor for vehicle without air supply.**

## Armrests

Part #	Fig.#	Color / Material	Description
1234231-544	--	Black / Vinyl	Left or Right Armrest
1234231-550	--	Black / Cloth	Left or Right Armrest
1234231-552	--	Gray / Cloth	Left or Right Armrest



Fig. 4



# WIPER BLADES

## Wiper Blades - Heavy Duty

Part #	Description	Length
717-20	20 Goodyear, HD	20"
717-22	22 Goodyear, HD	22"
717-24	24 Goodyear, HD	24"
717-26	26 Goodyear, HD	26"
717-28	28 Goodyear, HD	28"
717-32	32 Goodyear, HD	32"
718-32	32 Goodyear, HD	32"
718-36	36 Goodyear, HD	36"
718-37	36 Goodyear, HD	36"
718-40	40 Goodyear, HD	40"
718-41	40 Goodyear, HD	40"



## Wiper Blades - Premium

Part #	Description	Length
728-11	11 Goodyear	11"
728-12	12 Goodyear	12"
728-13	13 Goodyear	13"
728-14	14 Goodyear	14"
728-15	15 Goodyear	15"
728-16	16 Goodyear	16"
728-17	17 Goodyear	17"
728-18	18 Goodyear	18"
728-19	19 Goodyear	19"
728-20	20 Goodyear	20"
728-21	21 Goodyear	21"
728-22	22 Goodyear	22"
728-24	24 Goodyear	24"
728-26	26 Goodyear	26"
728-28	28 Goodyear	28"



## Aquapel

Part #	Fig.#	Description
AQ47100	1	Rain Repellent, Single Application
AQ98994	1	Rain Repellent, 24 Pack
TTW-148	---	Windshield Wash Premix



Fig. 1



# EXHAUST



Fig. 1



Fig. 2




Fig. 3




Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8

## Tubing (Sold Per Foot)

Part #	Fig.#	Dia.	Description
<b>Flexible</b>			
W49029	1	3.5" I.D.	Galvanized
W40011	1	4" I.D.	Galvanized
W40012	1	5" I.D.	Galvanized
W49034	1	4" I.D.	Stainless Steel
W40023	1	5" I.D.	Stainless Steel
<b>Straight</b>			
W49011	2	3.5" O.D.	Non-Bendable
W49012	2	4" O.D.	Non-Bendable
W49015	2	5" O.D.	Non-Bendable

## Aluminized Elbows

Part #	Fig.#	Dia.(ID/OD)	A-Length	B-Length	R-Radius
<b>45° Elbow</b>					
89780A	3	4"	6.5"	---	6"
89781A	3	5"	7.28"	---	5.5"
<b>90° Elbow</b>					
89105A	4	4"	10"	10"	6"
89106A	4	4"	18"	18"	6"
89107A	4	5"	15"	15"	8"
89784A	4	5"	10"	10"	8"
89924A	4	5"	8.5"	8.5"	5.5"

## Clamps

	Easy-Seal	Flat Band	Guillotine	Torc-Tite
Diameter	Fig.# 5	Fig.# 6	Fig.# 7	Fig.# 8
3.5"	89526K	89557K	89547K	90355A
4"	89527K	89558K	89548K	90356A
5"	89528K	89559K	89549K	90358A



# ABSORBENTS

## Spill Kits

Part #	Fig.#	Description
SP20	1	Economy Kit, Oil Only
SP2U	1	Economy Kit, Universal

**Contains: 10 Pads, 3 Socks (3" x 48"), 1 Disposal Bag, Zip Tie, 1 Pair Nitrile Gloves & Instruction Sheet**



Fig. 1

KT-50	2	5 Gal. Bucket, Oil Only
KT-5U	2	5 Gal. Bucket, Universal

**Contains: 10 Pads, 2 Socks (3" x 48"), 5 lbs. Ultrasorb, Disposal Bag, Zip Tie, 1 Pair Nitrile Gloves & Instruction Sheet**



Fig. 2

WPF100H-BX	3	Heavy-Duty Pads, Oil Only, 100/Box
GPF100H-BX	3	Heavy-Duty Pads, Universal, 100/Box
WP100S	---	Economy, Oil Only, 100/Bag



Fig. 3

Fig. 4

FD85	4	25lb. Floor Dry
------	---	-----------------

## Filters



**Heavy Duty Filtration For Lube, Fuel, Coolant and Hydraulic Systems.**



**All Popular Applications In Stock!**



# WARNING PRODUCTS



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9

## Back-Up Alarms

Part #	Fig.#	Voltage	dB	Description
505	1	12-24	87	Compact Size and Self Grounding
510	1	12	97	Sealed For Dust Protection
520	1	12-24	97	Compact Size and Self Grounding
530	1	12-24	102	Sealed For Dust Protection
575	1	12-24	107	Compact Size and Self Grounding

## Smart Alarms

SA-901	2	12-24	82-107	Self Adjusting
SA-917	2	12-24	87-112	Self Adjusting with Steel Housing

## Rotating Minibar

Part #	Fig.#	Voltage	FPM	Description
5135A	3	12	480	15" Low Profile w/ Permanent Mount
5135A-VM	4	12	480	15" Low Profile w/ Magnet Mount
5188CA		12		15" w/ Permanent Mount
5315A	5	12	300	15" w/ Permanent Mount
5315A-VM	6	12	300	15" w/ Vacuum Magnet Mount

## Flashing Minibar

Part #	Fig.#	Voltage	FPM	Description
5188CA		12		15" Low Profile w/ Permanent Mnt.

## LED Directional Lights

Part #	Fig. #	Voltage	FPM	Description
3710A		12	S/D/Q/Q	Surface Mount
3810A		12	Q	Surface Mount
3860A		12	Q	Surface Mount

## Rotating Beacons

Part #	Fig. #	Voltage	FPM	Description
5715A	7	12	100	3-Bolt Mount Rotating Beacon
5813A	8	12	160	3-Bolt Mount Rotating Beacon
5813A-MG	9	12	160	Magnet Mount Beacon

A = Amber

FPM = Flashes Per Minute



# WARNING PRODUCTS

## Strobe Beacons

Part #	Fig.#	Voltage	FPM	Description
6220A	1	12-80	85	2-Bolt Low Intensity Industrial Strobe
6400A	2	12-80	70	Low Profile w/ 3-Bolt Flange Mount
6410A	2	12-80	70	Low Profile w/ 3-Bolt Flange Mount
6410A-MG	3	12-80	70	Low Profile w/ Magnet Mount
6520A	---	12-48	80	Low Profile w/ 2-Bolt Flange Mount
6550A	4	12-48	D/Q	Low Profile w/ 3-Bolt or 1" Pipe Mount
6570A	---	12-48	D/Q	Med. Profile w/ 2-Bolt Flange Mount
7960A	---	12-24		Low Profile w/ Hi/Lo Intensity Control



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5

## Switchable Intensity Strobes

6650A	4	12-24	D/Q	Low Profile w/ 3-Bolt or 1" Pipe Mount
6670A	5	12-24	D/Q	Med. Profile w/ 3-Bolt or 1" Pipe Mount
6970A	---	12-24	D/Q	Med. Profile w/ 3-Bolt or 1" Pipe Mount

## Severe Vibration Strobes with Aluminum Base

6710A	---	12-48	D/Q	Low Profile w/ 3-Bolt or 1" Pipe Mount
6750A	4	12-24	D/Q	Low Profile w/ 3-Bolt or 1" Pipe Mount
6770A	5	12-24	D/Q	Med. Profile w/ 3-Bolt or 1" Pipe Mount

A = Amber      D/Q = Double or Quad Flash      FPM = Flashes Per Minute  
Other Lens Colors Available

## Lighting Accessories

Part #	Fig.#	Description
R5012BH	6	12-Volt Bulb for 5315/5700 Series
R5812BH	7	12-Volt Bulb for 5135/5800 Series
R6200FT	8	Flashtube for 6200 Series
R6410FT	9	Flashtube for 6400 Series
R6501FT	10	Flashtube for 6500/6600/6700 Series
R6600FT	---	Flashtube for 6600/6800 Series
A6600MK	11	Magnet Mount Kit
SW15	---	Universal Mechanical Switch



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11

